

BLOS	Beyond Line Of Sight
EPLRS	Enhanced Position Location Reporting System self-healing mesh network, automatic relaying
FT	Free Text (format)
FWF	Fixed Word Format J-series messages are always in FWF
IFDL	Intra Flight Data Link between F-22 fighters, maintaining LPI & LPD
JREAP	Joint Range Extension Protocol JREAP-A (Satellite) -B (Point to Point) - C (IP networks)
JTIDS	Joint Tactical Information Distribution System terminal (L16)
LINK 11	TDL or Tactical Data Link (TDL) A is primarily surface based, runs on 8bit computers
LINK 16	TDL 16bit, 127 nets maximum (0-126), 98.304 time slots per epoch per net information exchange via J-series messages
LINK 22	TDL BLOS, multiple nets, uses TDL-J series (L16 data dictionary)
LPD	Low Probability of Detection
LPI	Low Probability of Intercept
MADL	Multi-Function Advance Data Link provides LPI & LPD between stealth aircraft
MIDS	Multifunction Information Distribution System terminal (L16), has replaced most JTIDS / legacy systems employs MIDS-A or MIDS-B crypto
NTDS	Naval Tactical Data System Link 11
PLRS	Position Location Reporting System precursor to EPLRS
PPLI	Precise Participant Location & Identification
RTT	Round-Trip Timing (format)
SADL	Situation Awareness Data Link “blue force tracking”
S-TADIL J	Satellite Link 16 (USN)
TDMA	Time Division Multiple Access <i>architecture</i> delivering 128 time slots per second
VMF	Variable Message Format